



making work easy

Overview Renfert extraction units for CAM milling machines

Status: 24.04.2024



Performance Data	SILENT compactCAM	SILENT powerCAM TC	SILENT powerCAM EC
Volume Flow (max.)	2,500 l/min / 1.47 ft ³ /s	3,980 l/min / 2,34 ft ³ /s	3,984 l/min / 2.34 ft ³ /s
Suction Power	27 m/s	36 m/s	28 & 36 m/s
Max. Depression	219 hPa / 3.2 psi	281 hPa / 4,1 psi	257 hPa / 3.73 psi (230 V) 262 hPa / 3.8 psi (120 V) 255 hPa / 3.7 psi (100 V)
Guaranteed motor lifetime	1,000 h	1,000 h	5,000 h



The SILENT compactCAM, powerCAM TC & powerCAM EC are particle and dust extraction units especially designed for CAD/CAM milling machines. The SILENT compactCAM, powerCAM TC & powerCAM EC are compatible with CAD/CAM milling machines where:

1. The CAM manufacturer's technical requirements for extraction units are fulfilled.
2. The SILENT compactCAM / powerCAM TC / powerCAM EC can be switched on/off either manually or over the Renfert interface cable. Never switch the extraction units on/off when they are connected to the electrical relay control of the CAM machine. Doing so can lead to serious damage of the extraction units.
3. The list of extraction unit models is for orientation purposes only. As the requirements of the particular milling machine are important in selecting the correct extraction unit, please consult the CAM manufacturer.

Page 2	Page 3	Page 4	Page 5	Page 6	Page 7	Page 8
Amann-Girrbach > ARUM > cadblu > Canon > DEGOS Dental > Dentsply Sirona >	Ernst Hinrich GmbH > FINO > Goldquadrat >	imes-icore > ivoclar Vivadent > ORIGIN > Planmeca > Preciso Dental (Jensen) >	ProTechno (Ceratomic) > R & K > Redon > Roland DG/DGShape > Schütz Dental > Shera >	Siladent > Tissi Dental > Up3D > vhf >	Wieland > Yenadent > YETI Dental > XTCERA >	88Dent > ZIRKONZAHN >



making work easy

<6 hrs/
day
Low
workload

<6 hrs/
day
Medium
workload

>6 hrs/
day
Strong
workload

CAM Manufacturer	CAM System	SILENT compact CAM	SILENT powerCAM TC	SILENT powerCAM EC	Renfert Interface Cable		Comments			
					Type	Art. No.				
Amann-Girrbach	ceramill motion matik	●	●	●		D	29340009			
	ceramill motion mikro 4X/5X	●	●	●						
	ceramill motion 2 4X/5X	●	●	●						
	ceramill motion mikro ic							wet processing – no extraction unit necessary		
ARUM	5X-200	●	●	●		F	29340011			
	5X-300 Pro	●	●	●						
	4X-300 / 4X-300D	●	●	●				F + C14	29340012	For mills with C14 socket to connect with the extraction unit
	4X-100	●	●	●						
cadblu	ezMILL 4.0	●	●	●		A	29340005			
	ezMILL 5.0		●	●						
	ezMILL 5.DC		●	●						
Canon	MD-500	●	●	●		J	29340018			
DEGOS Dental	DEGOS STAR Z-MILL 255 N5	●	●	●		E	29340010	incl. NEMA adapter		
	DEGOS STAR Z-MILL 355 N5	●	●	●						
	DEGOS STAR Z-MILL 355 X6		●	●						
Dentsply Sirona	MC X5		●	●		H	29340016			
	MC XL	●								



Back



making work easy

< 6 hrs/
day
Low
workload

< 6 hrs/
day
Medium
workload

> 6 hrs/
day
Strong
workload

CAM Manufacturer	CAM System	SILENT compact CAM	SILENT powerCAM TC	SILENT powerCAM EC	Renfert Interface Cable		Comments
					Type	Art. No.	
Ernst Hinrichs GmbH	HinriMill 4 / 4 Edition	●	●	●		A	29340005
	HlinriMill 5		●	●			
	HlinriMill 5.8 / 5.8 Edition		●	●			
	HinriMill T5 / T5 Edition		●	●		G	29340013
	HinriMill R5		●	●			
	HinriMill Z4		●	●			
	HinriMill N4						
FINO	FINOCAM Kompakt A	●	●	●		A	29340005
	FINOCAM Kompakt M	●	●	●			
	FINOCAM Edition	●	●	●			
	FINOCAM CA		●	●			
	FINOCAM CA+		●	●		G	29340013
	FINOCAM PREMIUM		●	●			
	FINOCAM A5 / A5+		●	●			
	FINOCAM W						
Goldquadrat	Quattro Mill easy	●	●	●		A	29340005
	Quattro Mill Comfort	●	●	●			
	Quattro Mill PreFour	●	●	●			
	Quattro Mill Maxi		●	●		G	29340013
	GQ Quattro Mill R5		●	●			
	GQ Quattro Mill Comfort 5x Plus		●	●			
	VHF Z4						

Back



making work easy

<6 hrs/
day
Low
workload

<6 hrs/
day
Medium
workload

>6 hrs/
day
Strong
workload

CAM Manufacturer	CAM System	SILENT compact CAM	SILENT powerCAM TC	SILENT powerCAM EC	Renfert Interface Cable		Comments
					Type	Art. No.	
imes-icore	CORiTec one	●	●	●		C	29340008
	CORiTec 140i	●	●	●			
	CORiTec 150i	●	●	●			
	CORiTec 245i	●	●	●			
	CORiTec 250i	●	●	●			
	CORiTec 350i		●	●			
	CORiTec 350i Loader		●	●			
	CORiTec 650i		●	●			
	CORiTec 650i Loader		●	●			
Ivoclar Vivadent	Programill DRY		●	●		G	29340013
	PM7		●	●			
	PM5		●	●			
	PM3		●	●			
ORIGIN	ORIGIN 40	●	●	●		E	29340010
Planmeca	PlanMill 50	●	●	●		C	29340008
	PlanMill 40						
Preciso Dental (Jensen)	Preciso M200 Mill	●	●	●		A	29340005
	Roland DWX-50	●	●	●			

Back



making work easy

< 6 hrs/
day
Low
workload

< 6 hrs/
day
Medium
workload

> 6 hrs/
day
Strong
workload

CAM Manufacturer	CAM System	SILENT compact CAM	SILENT powerCAM TC	SILENT powerCAM EC	Renfert Interface Cable		Comments
					Type	Art. No.	
ProTechno (Ceratomic)	Ceratomic MAG 4	●	●	●		C	29340008
	Ceratomic MAG 5	●	●	●			
R & K	Organical Desktop 1	●	●	●		A	29340005
	Organical Desktop 3	●	●	●			
	Organical Desktop 7c	●	●	●			
Redon	GTR		●	●		F	29340011
RolandDG/DGShape	DWX-50	●	●	●		B	29340006
	DWX-4	●	●	●			
	DWX-51D	●	●	●			
	DWX-52D	●	●	●			
	DWX-52DCi		●	●		K	29340019
	DWX-53DC		●	●			
	DWX-4W						
	DWX-42W						
Schütz Dental	Tizian Cut compact	●	●	●		A	29340005
	Tizian Cut 5 dry		●	●		G	29340013
	Tizian Cut 5.2/5.2 Pro		●	●		C	29340008
	CORITEC 650i Loader		●	●			
Shera	SHERAeco-mill 40/50	●	●	●		A	29340005
	SHERAeco-mill 5x	●	●	●			

Back



making work easy

< 6 hrs/
day
Low
workload

< 6 hrs/
day
Medium
workload

> 6 hrs/
day
Strong
workload

CAM Manufacturer	CAM System	SILENT compact CAM	SILENT powerCAM TC	SILENT powerCAM EC	Renfert Interface Cable		Comments			
					Type	Art. No.				
Siladent	SilaMill 4 / 4 Edition	●	●	●		A	29340005			
	SilaMill 5		●	●						
	SilaMill 5.8		●	●						
	Silamill E5	●	●	●		G	29340013			
	SilaMill R5		●	●						
	SilaMill T5/ST5	●	●	●						
	SilaMill N4 / Z4									wet processing – no extraction unit necessary
Tissi Dental	Mini Mill 4 / plus 4	●	●	●		A	29340005			
	Mini Mill plus 5	●	●	●						
	Mini Mill plus 5A	●	●	●						
Up3D	P53		●	●		I	29340017			
vhf	K4 Impression	●	●	●		A	29340005			
	K4 edition	●	●	●						
	S1 Impression		●	●						
	S2 Impression		●	●						
	E4	●	●	●		G	29340013			
	E5	●	●	●						
	K5/K5+	●	●	●						
	S5		●	●						
	R5		●	●						
	Z4									
	N4 Impression									

Back



making work easy

< 6 hrs/
day
Low
workload

< 6 hrs/
day
Medium
workload

> 6 hrs/
day
Strong
workload

CAM Manufacturer	CAM System	SILENT compact CAM	SILENT powerCAM TC	SILENT powerCAM EC	Renfert Interface Cable		Comments
					Type	Art. No.	
Wieland	Zenotec mini	●	●	●		A	29340005
	Zenotec select ion		●	●			
	Zenotec select hybrid		●	●			
XTCERA	500SE	●	●	●		M	29340021
	500plus	●	●	●			
	520DC		●	●			
	580DC		●	●			
YenaDent	D10	●	●	●		E	29340010
	D14	●	●	●			
	D15	●	●	●			
	D16		●	●			
	D6		●	●			
	DC40		●	●			
	D43		●	●			
Yeti	digi MILL 4 dry	●	●	●		A	29340005
	digi MILL 5 dry		●	●			
	digi MILL 4 wet						

Back







making work easy

<6 hrs/
day
Low
workload

<6 hrs/
day
Medium
workload

>6 hrs/
day
Strong
workload


CAM Manufacturer	CAM System	SILENT compact CAM	SILENT powerCAM TC	SILENT powerCAM EC	Renfert Interface Cable		Comments	
					Type	Art. No.		
Zirkonzahn	M1 Soft	●	●	●		F	29340011	29340011 Interface cable Type F for Zirkonzahn. For all Zirkonzahn models equipped with a Schuko socket to connect with the extraction unit.
	M1 Wet Heavy Metal	●	●	●				
	M2 Wet Heavy Metal	●	●	●				
	M2 Teleskoper	●	●	●				
	M2 Dual Wet Heavy Metal	●	●	●				
	M2 Dual Teleskoper	●	●	●				
	M2 Dual Double Teleskoper	●	●	●		F + C14	29340012	29340012 Interface cable Type F for Zirkonzahn incl. C14-Adapter. For all Zirkonzahn models equipped with a Plug C14 according to IEC-6320 to connect with the extraction unit (e.g. USA) 
	M3	●	●	●				
	M4 Wet Heavy Metal		●	●				
	M5 Heavy Metal		●	●				
	M6 Wet Heavy Metal		●	●				
	M1 Abutment							
	M1 Wet							wet processing – no extraction unit necessary
88Dent	88Mill 4	●	●	●		A	29340005	
	88MILL 5		●	●				
	Esse 5		●	●				
	Erre 5		●	●		G	29340013	
	Mill Five S		●	●				
	Zeta 4		●	●				
	Kappa 5+		●	●				
	Enne 4+							wet processing – no extraction unit necessary

 Back



making work easy

Selection of the appropriate CAM extraction SILENT powerCAM EC or TC?

> 11 h/day	8 h/day	5 h/day	2.5 h/day	1 h/day	years	
 SILENT powerCAM EC					1	
					2	
						3
						4
						5
						6
						7
						8
						9
						10



SILENT powerCAM TC