

Page 1/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2023

Version number 6 (replaces version 5)

Revision: 08.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
  - · Trade name: Flexitime Easy Putty Base (1:1), Flexitime Dynamix Putty Base (5:1)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
  - · Application of the substance / the mixture Dental impression material
- · 1.3 Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

- Informing department: E-Mail: msds@kulzer-dental.com
- · 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
  - Classification according to Regulation (EC) No 1272/2008
    The product is not classified, according to the GB CLP regulation.

Additional information:

Since the product is a medical device in the sense of Directive 93/42/EEC (MDD) or the Regulation (EU) 2017/745 (MDR), that is intended for the end user and is used invasively or with physical contact, it is exempted from the classification and labeling obligation according to Regulation (EC) 1272/2008.

- - Labelling according to Regulation (EC) No 1272/2008 Void
    - · **Hazard pictograms** Void
    - · Signal word Void
    - · Hazard statements Void
  - · Additional information: see 2.1
- · 2.3 Other hazards -
  - · Results of PBT and vPvB assessment
    - · **PBT:** Not applicable.
    - vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
  - Description: -

| Dangerous components:          |                                |               |
|--------------------------------|--------------------------------|---------------|
|                                | cristobalite                   | 50-75%        |
| EINECS: 238-455-4              | STOT RE 1, H372                |               |
|                                | octamethylcyclotetrasiloxane   | ≥0.025-<0.25% |
| EINECS: 209-136-7              | Flam. Liq. 3, H226             |               |
| Reg.nr.: 01-2119529238-36-xxxx | Repr. 2, H361f                 |               |
|                                | Aquatic Chronic 1, H410 (M=10) |               |
|                                | PBT; vPvB                      |               |

· Additional information For the wording of the listed hazard phrases refer to section 16.



Page 2/7

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2023

Version number 6 (replaces version 5)

# Trade name: Flexitime Easy Putty Base (1:1), Flexitime Dynamix Putty Base (5:1)

(Contd. of page 1)

Revision: 08.02.2023

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
  - After inhalation Supply fresh air; consult doctor in case of symptoms.
  - After skin contact If skin irritation continues, consult a doctor.
  - After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
  - Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
  - · Protective equipment: No special measures required.
  - Additional information -

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Avoid contact with eyes and skin.

- · 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

# SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Please observe the additional instructions in the product's instructions for use.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
  - - Requirements to be met by storerooms and containers: No special requirements.
    - Information about storage in one common storage facility: Not required.

(Contd. on page 3)



Page 3/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2023

Version number 6 (replaces version 5)

on 5) Revision: 08.02.2023

# Trade name: Flexitime Easy Putty Base (1:1), Flexitime Dynamix Putty Base (5:1)

(Contd. of page 2)

· Further information about storage conditions: None.

· 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Not required.

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Wash hands during breaks and at the end of the work.

· Breathing equipment: Not required.

· Hand protection

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

Eye/face protection Safety glasses

· Body protection: Light weight protective clothing

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Physical state Fluid · Colour: Violet

Smell: Characteristic Odour threshold: Not determined.

· Melting point/freezing point: · Boiling point or initial boiling point and

boiling point or initial boiling point and boiling range

· Flammability

· Lower and upper explosion limit

300 °C Not applicable.

Not determined

Lower: Not determined.Upper: Not determined.

(Contd. on page 4)



Page 4/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2023 Version number 6 (replaces version 5) Revision: 08.02.2023

Trade name: Flexitime Easy Putty Base (1:1), Flexitime Dynamix Putty Base (5:1)

(Contd. of page 3) >130 °C · Flash point: Decomposition temperature: Not determined. SADT pН Not determined. . Viscosity: Kinematic viscosity Not determined. Not determined. · dynamic: Solubility Water: Not miscible or difficult to mix · Partition coefficient n-octanol/water (log Not determined. value) Steam pressure: Not determined. Density and/or relative density Density Not determined Relative density Not determined. · Vapour density Not determined. · 9.2 Other information No further relevant information available. Appearance: . Form: Pasty · Important information on protection of health and environment, and on safety. Product is not selfigniting. · Self-inflammability: · Explosive properties: Product is not explosive. Not determined. · Solvent content: 58.2 % Solids content: Change in condition Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases · Gases under pressure Void Void Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void Organic peroxides Corrosive to metals Void Void · Desensitised explosives Void



Page 5/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2023

Version number 6 (replaces version 5)

Trade name: Flexitime Easy Putty Base (1:1), Flexitime Dynamix Putty Base (5:1)

(Contd. of page 4)

Revision: 08.02.2023

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
  - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
  - · Additional information: -

### **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
  - · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/      | LD/LC50 values that are relevant for classification: |                                 |  |  |  |  |
|------------|--|---------------------------------|--|--|--|--|
| 68083-19-  | 68083-19-2 Silopren U 1 dental                       |                                 |  |  |  |  |
| Oral       | Oral LD50 >5000 mg/kg (rat)                          |                                 |  |  |  |  |
| 8042-47-5  | White n  | nineral oil, petroleum          |  |  |  |  |
| Oral       | LD50   | >5000 mg/kg (rat) (OECD 401)    |  |  |  |  |
| Dermal     | LD50   | >2000 mg/kg (rabbit) (OECD 402) |  |  |  |  |
| Inhalative | LC0/4h   | ≥5 mg/L (rat) (OECD 403)        |  |  |  |  |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
  - · Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
  - · Aquatic toxicity:

# 8042-47-5 White mineral oil, petroleum

LL50/96h >100 mg/L (fish) (OECD 203)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
  - · PBT: Not applicable.
  - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 6)



Page 6/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2023

Version number 6 (replaces version 5)

Revision: 08.02.2023

# Trade name: Flexitime Easy Putty Base (1:1), Flexitime Dynamix Putty Base (5:1)

(Contd. of page 5)

#### · 12.7 Other adverse effects

- Additional ecological information:
  - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
  - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packagings:
  - Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

| SECTION 14: Transport information                    |                                  |  |
|--|----------------------------------|--|
| · 14.1 UN number or ID number<br>· ADR, IMDG, IATA   | Void                             |  |
| · 14.2 UN proper shipping name<br>· ADR, IMDG, IATA  | Void                             |  |
| · 14.3 Transport hazard class(es)                    |                                  |  |
| ADR, ADN, IMDG, IATA<br>Class                        | Void                             |  |
| · 14.4 Packing group<br>· ADR, IMDG, IATA            | Void                             |  |
| · 14.5 Environmental hazards:<br>· Marine pollutant: | No                               |  |
| · 14.6 Special precautions for user                  | Not applicable.                  |  |
| · 14.7 Maritime transport in bulk accordin           | n <b>g to</b><br>Not applicable. |  |
| · Transport/Additional information:                  | -                                |  |
| UN "Model Regulation":                               | Void                             |  |

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Directive 2012/18/EU
    - · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 7)



Page 7/7

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2023

Version number 6 (replaces version 5)

Trade name: Flexitime Easy Putty Base (1:1), Flexitime Dynamix Putty Base (5:1)

(Contd. of page 6)

Revision: 08.02.2023

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H361f Suspected of damaging fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3
Repr. 2: Reproductive toxicity – Category 2
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

\* Data compared to the previous version altered.



Page 1/7

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 09.02.2023

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
  - · Trade name: Flexitime Easy Putty Cat. (1:1), Flexitime Dynamix **Putty Cat. (5:1)**
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
  - Application of the substance / the mixture Dental impression material
- · 1.3 Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

- Informing department: E-Mail: msds@kulzer-dental.com
- · 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
  - Classification according to Regulation (EC) No 1272/2008
    The product is not classified, according to the GB CLP regulation.

Additional information:

Since the product is a medical device in the sense of Directive 93/42/EEC (MDD) or the Regulation (EU) 2017/745 (MDR), that is intended for the end user and is used invasively or with physical contact, it is exempted from the classification and labeling obligation according to Regulation (EC) 1272/2008.

- - Labelling according to Regulation (EC) No 1272/2008 Void
    - · Hazard pictograms Void
    - · Signal word Void
    - · Hazard statements Void
  - · Additional information: see 2.1
- · 2.3 Other hazards -
  - · Results of PBT and vPvB assessment
    - · PBT: Not applicable.
    - vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
  - · Description: -

· Dangerous components:

CAS: 14464-46-1 cristobalite

EINECS: 238-455-4

STOT RE 1. H372

50-75%

· Additional information For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
  - After inhalation Supply fresh air; consult doctor in case of symptoms.
  - After skin contact If skin irritation continues, consult a doctor.
  - After eve contact

Rinse opened eye for several minutes under running water. Then consult doctor.

(Contd. on page 2)



Page 2/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Trade name: Flexitime Easy Putty Cat. (1:1), Flexitime Dynamix Putty

Cat. (5:1)

(Contd. of page 1)

Revision: 09.02.2023

After swallowing

Rinse out mouth and then drink plenty of water. In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
  - · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
  - · Protective equipment: No special measures required.
  - · Additional information -

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Avoid contact with eyes and skin.

- · 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Please observe the additional instructions in the product's instructions for use.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
  - · Storage
    - · Requirements to be met by storerooms and containers: No special requirements.
    - Information about storage in one common storage facility: Not required.
    - · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

GB



Page 3/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 09.02.2023

Trade name: Flexitime Easy Putty Cat. (1:1), Flexitime Dynamix Putty Cat. (5:1)

(Contd. of page 2)

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Not required.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
  - Appropriate engineering controls No further data; see item 7.
  - Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Not required.
- Hand protection

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

- · Eye/face protection Safety glasses
- · Body protection: Light weight protective clothing

#### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Physical state Fluid · Colour: White

Smell: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Not determined

Melting point/freezing point:
 Boiling point or initial boiling point and

boiling range
Not determined
Not applicable.

· Lower and upper explosion limit

· Lower:
 · Upper:
 · Very Park Point:
 · Lower:
 · Not determined.
 · Flash point:
 > 130 °C

Decomposition temperature: Not determined.

SADT Not determined.

(Contd. on page 4)



Page 4/7

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2023 Version number 6 (replaces version 5) Revision: 09.02.2023

Trade name: Flexitime Easy Putty Cat. (1:1), Flexitime Dynamix Putty Cat. (5:1)

(Contd. of page 3) · Viscosity: Kinematic viscosity Not determined. dynamic: Not determined. Solubility Water: Not miscible or difficult to mix Partition coefficient n-octanol/water (log Not determined. Not determined. · Steam pressure: · Density and/or relative density Density at 20 °C 1.6 g/cm3 · Relative density Not determined. · Vapour density Not determined. · 9.2 Other information No further relevant information available. Appearance: Pastv Form: · Important information on protection of health and environment, and on safety. Self-inflammability: Product is not selfigniting. Product is not explosive. Explosive properties: Not determined. · Solvent content: 62.7 % Solids content: Change in condition Evaporation rate Not determined. · Information with regard to physical hazard classes **Explosives** Void Void · Flammable gases · Aerosols Void Oxidising gases
Gases under pressure Void Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit Void flammable gases in contact with water · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
  - Conditions to be avoided: No decomposition if used and stored according to specifications.

Void

10.3 Possibility of hazardous reactions No dangerous reactions known

(Contd. on page 5)



Page 5/7

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 09.02.2023

# Trade name: Flexitime Easy Putty Cat. (1:1), Flexitime Dynamix Putty Cat. (5:1)

(Contd. of page 4)

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
  - Additional information: -

### SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

| · LD/      | · LD/LC50 values that are relevant for classification: |                                 |  |  |  |  |
|------------|--|---------------------------------|--|--|--|--|
| 68083-19-  | 68083-19-2 Silopren U 1 dental                         |                                 |  |  |  |  |
| Oral       | LD50   | >5000 mg/kg (rat)               |  |  |  |  |
| 8042-47-5  | White n  | nineral oil, petroleum          |  |  |  |  |
| Oral       | LD50   | >5000 mg/kg (rat) (OECD 401)    |  |  |  |  |
| Dermal     | LD50   | >2000 mg/kg (rabbit) (OECD 402) |  |  |  |  |
| Inhalative | LC0/4h   | ≥5 mg/L (rat) (OECD 403)        |  |  |  |  |

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
  Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
  - Endocrine disrupting properties

None of the ingredients is listed.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
  - · Aquatic toxicity:

#### 8042-47-5 White mineral oil, petroleum

LL50/96h >100 mg/L (fish) (OECD 203)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
  - PBT: Not applicable.
  - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

(Contd. on page 6)



Page 6/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 09.02.2023

# Trade name: Flexitime Easy Putty Cat. (1:1), Flexitime Dynamix Putty Cat. (5:1)

(Contd. of page 5)

#### · 12.7 Other adverse effects

- Additional ecological information:
  - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
  - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packagings:
  - Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

| SECTION 14: Transport information                         | on                             |  |
|---|--------------------------------|--|
| 14.1 UN number or ID number<br>· ADR, IMDG, IATA          | Void                           |  |
| 14.2 UN proper shipping name<br>· ADR, IMDG, IATA         | Void                           |  |
| 14.3 Transport hazard class(es)                           |                                |  |
| · ADR, ADN, IMDG, IATA<br>· Class                         | Void                           |  |
| 14.4 Packing group<br>· ADR, IMDG, IATA                   | Void                           |  |
| 14.5 Environmental hazards: · Marine pollutant:           | No                             |  |
| 14.6 Special precautions for user                         | Not applicable.                |  |
| 14.7 Maritime transport in bulk according IMO instruments | <b>y to</b><br>Not applicable. |  |
| · Transport/Additional information:                       | -                              |  |
| · UN "Model Regulation":                                  | Void                           |  |

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Directive 2012/18/EU
    - · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 7)



Page 7/7

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2023

Version number 6 (replaces version 5)

Revision: 09.02.2023

Trade name: Flexitime Easy Putty Cat. (1:1), Flexitime Dynamix Putty Cat. (5:1)

(Contd. of page 6)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H372 Causes damage to organs through prolonged or repeated exposure.

#### Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement

Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

\* Data compared to the previous version altered.



Page 1/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
  - · Trade name: Universal Adhesive
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
  - Application of the substance / the mixture Tray adhesive for use with silicone impression materials
- · 1.3 Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· Informing department: E-Mail: msds@kulzer-dental.com

· 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
  - Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

H318 Eve Dam. 1 Causes serious eye damage.

Aquatic Chronic 3 H412 (M=10) Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

tetra-n-butoxytitanium

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

· 2.3 Other hazards -

(Contd. on page 2)



Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

# Trade name: Universal Adhesive

| Results | of PBT    | and | vPvB    | assessment |
|---------|-----------|-----|---------|------------|
|         | · · · — · |     | • • • • | 400000     |

(Contd. of page 1)

| P | R. | T· |
|---|----|----|

556-67-2 octamethylcyclotetrasiloxane

· vPvB:

556-67-2 octamethylcyclotetrasiloxane

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: -

| Description   |   |               |
|---|---|---------------|
| · Dangerous components:                             |   |               |
| EINECS: 205-500-4<br>Reg.nr.: 01-2119475103-46-xxxx | ethyl acetate<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319; STOT SE 3, H336<br>EUH066                                | ≥10-<20%      |
| EINECS: 215-535-7<br>Reg.nr.: 2119488216-32-xxxx    | xylene, mixed isomers, pure<br>Flam. Liq. 3, H226<br>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin<br>Irrit. 2, H315 | ≥0-<10%       |
| EINECS: 227-006-8                                   | tetra-n-butoxytitanium<br>Flam. Liq. 3, H226<br>Eye Dam. 1, H318<br>Skin Irrit. 2, H315                             | ≥3-<5%        |
| EINECS: 202-849-4                                   | ethylbenzene<br>Flam. Liq. 2, H225<br>STOT RE 2, H373; Asp. Tox. 1, H304<br>Acute Tox. 4, H332                      | ≥0-≤5%        |
| EINECS: 209-136-7<br>Reg.nr.: 01-2119529238-36-xxxx | octamethylcyclotetrasiloxane<br>Flam. Liq. 3, H226<br>Repr. 2, H361f<br>Aquatic Chronic 1, H410 (M=10)<br>PBT; vPvB | ≥0.025-<0.25% |

Additional information For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
  - · After inhalation Supply fresh air; consult doctor in case of symptoms.
  - · After skin contact If skin irritation continues, consult a doctor.
  - · After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

GB



Page 3/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

Trade name: Universal Adhesive

(Contd. of page 2)

# SECTION 5: Firefighting measures

- 5.1 Extinguishing media
  - · Suitable extinguishing agents
    - CO2, extinguishing powder or water jet. Fight larger fire with alcohol-resistant foam.
  - For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
  - · Protective equipment: No special measures required.
  - Additional information -

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

\_

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
  - · Storage
    - · Requirements to be met by storerooms and containers: Store in cool location.
    - · Information about storage in one common storage facility: Not required.
    - · Further information about storage conditions:
    - Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

CD.

(Contd. on page 4)



Page 4/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

Trade name: Universal Adhesive

(Contd. of page 3)

| 8.1 Contro                  | ol parameters   |                   |                                    |                                       |   |
|-----------------------------|-----------------|-------------------|------------------------------------|---------------------------------------|---|
| · Compo                     | onents with cri | itical valu       | es that require                    | monitoring at the workplace           | : |
|                             | ethyl acetate   |                   |                                    |                                       |   |
| WEL (Gre                    | at Britain)     |                   |                                    | ng/m³, 400 ppm                        |   |
| 10511475                    |                 | _                 | m value: 734 mg                    |                                       |   |
| IOELV (El                   | ıropean Union)  |                   | m value: 1468 r<br>n value: 734 mg | mg/m³, 400 ppm                        |   |
| 1330-20-7                   | xylene, mixed   |                   |                                    | улт , 200 ррт                         |   |
| WEL (Gre                    |                 |                   | m value: 441 m                     | g/m³. 100 ppm                         |   |
| 7722 (0.0                   | at 2man)        |                   | m value: 220 mg                    |                                       |   |
| IOELV (Ει                   | ıropean Union)  |                   | m value: 442 m                     |                                       |   |
|                             |                 | Long-terr<br>Skin | m value: 221 mg                    | g/m³, 50 ppm                          |   |
| 100-41-4                    | ethylbenzene    | JAIT              |                                    |                                       |   |
| WEL (Gre                    |                 | Short-ter         | m value: 552 m                     | g/m³. 125 ppm                         |   |
|                             | 2. 2            | Long-terr<br>Sk   | n value: 441 mg                    | g/m³, 100 ppm                         |   |
| IOELV (Ει                   | ıropean Union)  | Long-terr         | m value: 884 m<br>n value: 442 mg  | g/m³, 200 ppm<br>g/m³, 100 ppm        |   |
|                             |                 | Skin              |                                    |                                       |   |
| · DNI                       | ELs             |                   |                                    |                                       |   |
| 141-78-6 e                  | ethyl acetate   |                   |                                    |                                       |   |
| Oral                        |                 | _                 | -                                  | 4.5 mg/Kg (not defined)               |   |
| Dermal                      | worker industri | _                 | -                                  | 63 mg/Kg/d (not defined)              |   |
|                             |                 | _                 | term, systemic                     | · · · · · · · · · · · · · · · · · · · |   |
| Inhalative                  | worker industri |                   |                                    | 1,468 mg/m3 (not defined)             |   |
|                             | worker industri | ial, acute,       | local                              | 1,468 mg/m3 (not defined)             |   |
|                             | worker industri | ial, long te      | rm, systemic                       | 734 mg/m3 (not defined)               |   |
|                             | worker industri | ial, long te      | rm, local                          | 734 mg/m3 (not defined)               |   |
|                             | general popula  | ition, acute      | e, systemic                        | 734 mg/m3 (not defined)               |   |
|                             | general popula  | ntion, acute      | e, local                           | 734 mg/m3 (not defined)               |   |
|                             | general popula  | tion, long        | term, systemic                     | 367 mg/m3 (not defined)               |   |
|                             | general popula  | tion, long        | term, local                        | 367 mg/m3 (not defined)               |   |
| 556-67-2 d                  | octamethylcyc   | lotetrasilo       | oxane                              |                                       |   |
| Oral                        | general popula  | tion, long        | term, systemic                     | 3.7 mg/Kg (not defined)               |   |
| Inhalative worker industria |                 | ial, long te      | rm, systemic                       | 73 mg/m3 (not defined)                |   |
|                             | worker industri | ial, long te      | rm, local                          | 73 mg/m3 (not defined)                |   |
|                             | general popula  | tion, long        | term, systemic                     | 13 mg/m3 (not defined)                |   |
|                             | general popula  | tion, long        | term, local                        | 13 mg/m3 (not defined)                |   |
| ·PNE                        | ECs .           |                   |                                    |                                       |   |
| 141-78-6                    | ethyl acetate   |                   |                                    |                                       |   |
| freshwatei                  |                 |                   | 0.24 mg/l (not                     | dofinad)                              |   |



Page 5/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

# Trade name: Universal Adhesive

| _ |                                    | (Contd. of page 4)         |
|---|------------------------------------|----------------------------|
|   | sewage treatment plant             | 650 mg/l (not defined)     |
|   | sediment, dry weight, freshwater   | 1.15 mg/Kg (not defined)   |
|   | sediment, dry weight, marine water | 0.115 mg/Kg (not defined)  |
|   | soil, dry weight                   | 0.148 mg/Kg (not defined)  |
|   | 556-67-2 octamethylcyclotetrasilo  | oxane                      |
|   | freshwater                         | 0.0015 mg/l (not defined)  |
|   | marine water                       | 0.00015 mg/l (not defined) |
|   | sewage treatment plant             | 10 mg/l (not defined)      |
|   | sediment, dry weight, freshwater   | 3 mg/Kg (not defined)      |
|   | sediment, dry weight, marine water | 0.3 mg/Kg (not defined)    |
|   | · Ingredients with biological      | limit values:              |
|   | 1330-20-7 xylene, mixed isomers,   | pure                       |
|   | BMGV (Great Britain) 650 mmol/mo   |                            |
|   | Medium: urin                       | ~                          |
|   | Sampling tim                       | e: post shift              |
|   | Parameter: n                       | neṫhyl hippuric acid       |

· Additional information: The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· Hand protection

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

- Eye/face protection Tightly sealed safety glasses.
- · Body protection: Light weight protective clothing

- GF



Page 6/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

Trade name: Universal Adhesive

(Contd. of page 5)

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid · Colour: Blue · Smell: Ester-like

Odour threshold: Not determined. · Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

77 °C boiling range

· Flammability Not applicable.

· Lower and upper explosion limit

2.1 Vol % Lower: 11.5 Vol % Upper: 3°C Flash point:

460 °C Ignition temperature:

· Decomposition temperature: Not determined.

SADT

· pH · Viscosity: Not determined.

Kinematic viscosity Not determined. dynamic: Not determined.

Solubility

Not miscible or difficult to mix Water:

· Partition coefficient n-octanol/water (log

Not determined. value)

· Steam pressure at 20 °C: 102 hPa

Density and/or relative density

Density at 20 °C 1.20169 g/cm3 Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information No further relevant information available.

Appearance:

Fluid Form:

· Important information on protection of health and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures is possible.

· Solvent content:

0.0 % Solids content:

Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

**Explosives** Void · Flammable gases Void · Aerosols Void · Oxidising gases · Gases under pressure Void Void

· Flammable liquids Highly flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void

(Contd. on page 7)



Page 7/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

# Trade name: Universal Adhesive

|                                       |      | (Contd. of page 6) |
|---------------------------------------|------|--------------------|
| · Pyrophoric liquids                  | Void |                    |
| · Pyrophoric solids                   | Void |                    |
| Self-heating substances and mixtures  | Void |                    |
| · Substances and mixtures, which emit |      |                    |
| flammable gases in contact with water | Void |                    |
| · Oxidising liquids                   | Void |                    |
| · Oxidising solids                    | Void |                    |
| · Organic peroxides                   | Void |                    |
| · Corrosive to metals                 | Void |                    |
| · Desensitised explosives             | Void |                    |

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
  - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
  - · Additional information: -

### **SECTION 11: Toxicological information**

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 values that are relevant for classification: |            |                               |  |  |  |
|--|------------|-------------------------------|--|--|--|
| 141-78-6 ethyl acetate                                 |            |                               |  |  |  |
| Dermal LD50 >20,000 mg/kg (rabbit)                     |            |                               |  |  |  |
| 1330-20-7  | xylene, n  | nixed isomers, pure           |  |  |  |
| Oral   | LD50       | 8,700 mg/kg (rat)             |  |  |  |
| Dermal   | LD50       | 2,000 mg/kg (rabbit)          |  |  |  |
| Inhalative   | LC50/4 h   | 6,350 mg/l (rat)              |  |  |  |
| 100-41-4   | ethylbenze | ene                           |  |  |  |
| Oral   | LD50       | 3,500 mg/kg (rat)             |  |  |  |
| Dermal   | LD50       | 17,800 mg/kg (rabbit)         |  |  |  |
| 556-67-2 octamethylcyclotetrasiloxane                  |            |                               |  |  |  |
| Oral   | LD50       | >4,800 mg/kg (rat) (OECD 401) |  |  |  |
| Dermal   | LD50       | >2,375 mg/kg (rat) (OECD 402) |  |  |  |
| Inhalative   | LC50/4 h   | 36 mg/l (rat) (OECD 403)      |  |  |  |

- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

# Trade name: Universal Adhesive

(Contd. of page 7)

- · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
  - · Endocrine disrupting properties

None of the ingredients is listed.

· vPvB:

556-67-2 octamethylcyclotetrasiloxane

|               | 12: Ecological information                           |  |
|---------------|--|--|
| 12.1 Toxicity | •  |  |
| · Aquatic t   |  |  |
| 141-78-6 eth  |  |  |
|               | 230 mg/l (fish)                                      |  |
|               | 2.4 mg/l (daphnia) (OECD 211)                        |  |
|               | >100 mg/l (algae) (OECD 201)                         |  |
|               | ylene, mixed isomers, pure                           |  |
| LC50/96h      | 13.4 mg/l (fish)                                     |  |
| EC50          | 165 mg/l (daphnia)                                   |  |
|               | tamethylcyclotetrasiloxane                           |  |
| EC50/21d      | >0.015 mg/L (daphnia) (EPA OTS 797.1330)             |  |
| EC50/48h      | >0.015 mg/l (daphnia) (EPA OTS 797.1300)             |  |
| LC50/96h      | >0.022 mg/l (fish) (EPA OTS 797.1400)                |  |
|               | ≥0.0044 mg/l (fish)                                  |  |
|               | ≥0.015 mg/l (daphnia) (EPA OTS 797.1330)             |  |
| NOEC / 96h    | <0.022 mg/l (algae) (EPA OTS 797.1050)               |  |
|               | ≥0.022 mg/l (fish) (EPA OTS 797.1400)                |  |
|               | ≥0.015 mg/l (daphnia) (EPA OTS 797.1300)             |  |
|               | >0.022 mg/L (algae) (EPA OTS 797.1050)               |  |
|               | ence and degradability                               |  |
| 141-78-6 eth  |  |  |
| •             | ion 69 % /20d (not defined)                          |  |
| 100-41-4 eth  |  |  |
| •             | ion 68 % (not defined)                               |  |
|               | tamethylcyclotetrasiloxane                           |  |
| Biodegradati  | ion   3.7 % /29d (not defined) (OECD 310)            |  |
|               | umulative potential                                  |  |
| 141-78-6 eth  | nyl acetate  |  |
|               | ation factor (BCF)   30 (not defined)                |  |
|               | tamethylcyclotetrasiloxane                           |  |
|               | ation factor (BCF)   12,400 (not defined)            |  |
|               | y in soil No further relevant information available. |  |
| 12.5 Results  | s of PBT and vPvB assessment                         |  |



Page 9/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

# Trade name: Universal Adhesive

(Contd. of page 8)

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
  - Additional ecological information:
    - · General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
  - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
  - Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

| 14.1 UN number or ID number ADR, IMDG, IATA           | UN1866  |
|---|---|
| 14.2 UN proper shipping name<br>· ADR<br>· IMDG, IATA | 1866 RESIN SOLUTION, special provision 64<br>RESIN SOLUTION |
| 14.3 Transport hazard class(es)                       |   |
| · ADR   |   |
|   |   |
| · Class<br>· Label                                    | 3 (F1) Flammable liquids.<br>3                              |
| · IMDG, IATA  |   |
|   |   |
| · Class<br>· Label                                    | 3 Flammable liquids.<br>3                                   |
| 14.4 Packing group<br>· ADR, IMDG, IATA               | II .  |
| 14.5 Environmental hazards:  Marine pollutant:        | No  |
| 14.6 Special precautions for user                     | Warning: Flammable liquids.                                 |



Page 10/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

Trade name: Universal Adhesive

(Contd. of page 9) · Kemler Number:

F-E,S-E · EMS Number: Stowage Category В

· 14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

· Transport/Additional information:

· Limited quantities (LQ)

Excepted quantities (ÉQ) Code: E2

Maximum net quantity per inner packaging:

Maximum net quantity per outer packaging:

500 ml

· Transport category Tunnel restriction code D/E

·IMDG

· Limited quantities (LQ) 5L Excepted quantities (ÉQ) Code: E2

Maximum net quantity per inner packaging:

30 ml

Maximum net quantity per outer packaging:

500 ml

UN "Model Regulation": UN 1866 RESIN SOLUTION, SPECIAL

PROVISION 640D, 3, II

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Directive 2012/18/EU
    - · Named dangerous substances ANNEX I None of the ingredients is listed.
    - · Seveso category P5c FLAMMABLE LIQUIDS

    - Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
    - · Other regulations, limitations and prohibitive regulations
      - Substances of very high concern (SVHC) according to REACH, Article 57

556-67-2 octamethylcyclotetrasiloxane

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Harmful in contact with skin. H312

Causes skin irritation.

(Contd. on page 11)



Page 11/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2022 Version number 3 Revision: 03.08.2022

# Trade name: Universal Adhesive

\* Data compared to the previous version altered.

(Contd. of page 10) Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. H373 H410 Very toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Abbreviations and acronyms: SADT: Self Accelerating Decomposition Temperature ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods INDES: International Maritime Code to Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category ?

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB