

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GC RELINE II PRIMER FOR RESIN
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V.
Interleuvenlaan 33
B-3001 Leuven
Tel. +32/(0)16/74.10.00
Fax +32/(0)16/40.26.84
msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device. The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl acetate ethyl acetate

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

9 % of the mixture consists of component(s) of unknown toxicity.

Contains 9 % of components with unknown hazards to the aquatic environment.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:	Dangerous components:			
CAS: 79-20-9	methyl acetate	50-<75%		
EINECS: 201-185-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336			
Index number: 607-021-00-X				
CAS: 141-78-6	ethyl acetate	25-<50%		
EINECS: 205-500-4	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336			
Index number: 607-022-00-5				

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:

Protect unharmed eye.

(Contd. on page 3)

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

(Contd. of page 2)

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

 $Dispose\ of\ the\ material\ collected\ according\ to\ regulations.$

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

(Contd. of page 3)

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

79-20-9 methyl acetate

WEL Short-term value: 770 mg/m³, 250 ppm Long-term value: 616 mg/m³, 200 ppm

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


(Contd. on page 5)

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

(Contd. of page 4)

· Eye protection:



PH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: 77 °C Flash point: -10 °C Flammability (solid, gas): Not application temperature: Undet Decomposition temperature: Not def Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not def Density at 20 °C: Relative density Not def Vapour density Not def	ike termined. plicable. ermined. termined. termined. termined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Appearance: Form: Form: Colour: Odour: Odour threshold: PH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability (solid, gas): Not application temperature: Undet Decomposition temperature: Not de Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: Relative density Not de Evaporation rate Not de Not de Not de	termined. termined. plicable. ermined. termined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Form: Fluid Colour: Clear Odour: Fruit- Odour threshold: Not de pH-value: Not de Change in condition Melting point/freezing point: -83 °C Initial boiling point and boiling range: 77 °C Flash point: -10 °C Flammability (solid, gas): Not ap Ignition temperature: Undet Decomposition temperature: Not de Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: 2.1 Vo Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: 0.9 g/c Relative density Not de Vapour density Not de Evaporation rate Not de	termined. termined. plicable. ermined. termined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Colour: Odour: Odour threshold: PH-value: Not despendent of the point	termined. termined. plicable. ermined. termined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Odour: Odour threshold: Not deepH-value: Initial boiling point and boiling range: 77 °C Flash point: -10 °C Flammability (solid, gas): Not application temperature: Undet Decomposition temperature: Not deepH-value: Not deepH-val	termined. termined. plicable. ermined. termined. termined. ct is not selfigniting. ct does not present an explosion hazard.
pH-value: Change in condition Melting point/freezing point: Initial boiling point and boiling range: 77 °C Flash point: -10 °C Flammability (solid, gas): Not application temperature: Undet Decomposition temperature: Not def Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not def Density at 20 °C: Relative density Not def Vapour density Not def Evaporation rate	plicable. ermined. termined. termined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Change in condition Melting point/freezing point: Initial boiling point and boiling range: 77 °C Flash point: Flammability (solid, gas): Not ap Ignition temperature: Undet Decomposition temperature: Produ Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: Relative density Not de Vapour density Not de Evaporation rate Not de	plicable. ermined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Melting point/freezing point: Initial boiling point and boiling range: 77 °C Flash point: -10 °C Flammability (solid, gas): Not application temperature: Undet Decomposition temperature: Not det Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not det Density at 20 °C: Relative density Not det Vapour density Not det Evaporation rate Not det	plicable. ermined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Initial boiling point and boiling range: 77 °C Flash point: -10 °C Flammability (solid, gas): Not ap Ignition temperature: Undet Decomposition temperature: Not de Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: 2.1 Vo Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: 0.9 g/G Relative density Not de Vapour density Not de Evaporation rate	plicable. ermined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Flash point: Flammability (solid, gas): Not ap Ignition temperature: Undet Decomposition temperature: Not de Auto-ignition temperature: Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: Relative density Not de Vapour density Not de Evaporation rate	plicable. ermined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Flammability (solid, gas): Not ap Ignition temperature: Undet Decomposition temperature: Not de Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: Relative density Not de Vapour density Not de Evaporation rate Not de	plicable. ermined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Ignition temperature: Decomposition temperature: Not de Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: Relative density Not de Vapour density Not de Evaporation rate	ermined. termined. ct is not selfigniting. ct does not present an explosion hazard.
Decomposition temperature: Auto-ignition temperature: Explosive properties: Produ Explosion limits: Lower: Upper: Vapour pressure: Not de Density at 20 °C: Relative density Not de Vapour density Not de Evaporation rate	termined. ct is not selfigniting. ct does not present an explosion hazard.
Auto-ignition temperature: Produ Explosive properties: Produ Explosion limits: Lower: 2.1 Vo Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: 0.9 g/o Relative density Not de Vapour density Not de Evaporation rate Not de	ct is not selfigniting. ct does not present an explosion hazard.
Explosive properties: Produ Explosion limits: Lower: 2.1 Vo Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: 0.9 g/c Relative density Not de Vapour density Not de Evaporation rate Not de	ct does not present an explosion hazard.
Explosion limits: 2.1 Vo Lower: 2.1 Vo Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: 0.9 g/o Relative density Not de Vapour density Not de Evaporation rate Not de	1%
Lower: 2.1 Vo Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: 0.9 g/c Relative density Not de Vapour density Not de Evaporation rate Not de	
Upper: 16.0 V Vapour pressure: Not de Density at 20 °C: 0.9 g/c Relative density Not de Vapour density Not de Evaporation rate Not de	
Vapour pressure: Density at 20 °C: Relative density Not de Vapour density Not de Evaporation rate Not de	ol %
Density at 20 °C:0.9 g/cRelative densityNot deVapour densityNot deEvaporation rateNot de	
Relative densityNot deVapour densityNot deEvaporation rateNot de	termined.
Vapour densityNot deEvaporation rateNot de	m^3
Evaporation rate Not de	termined.
<u> </u>	termined.
Solubility in / Miscibility with	termined.
water: Fully i	niscible.
Partition coefficient: n-octanol/water: Not de	termined.
Viscosity:	
_ 5	termined.
Kinematic: Not de	termined.
Solvent content:	
Organic solvents: 91.0 % VOC (EC) 819.0	

 $(Contd.\ on\ page\ 6)$

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
79-20-9 m	79-20-9 methyl acetate		
Oral	LD50	6970 mg/kg (rat (f+m))	
141-78-6 е	141-78-6 ethyl acetate		
Oral	LD50	4935 mg/kg (rabbit)	
Inhalative	LC50/4 h	1600 mg/l (rat (f+m))	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 7)

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

(Contd. of page 6)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	· European	· European waste catalogue			
ſ		WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care)			
ŀ		wastes from natal care, diagnosis, treatment or prevention of disease in humans			
Γ	18 01 06*	chemicals consisting of or containing dangerous substances			

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION	<i>14:</i> 1	Transport	inf	ormat	ion

- · 14.1 UN-Number
- · ADR, IMDG, IATA

UN1173

- · 14.2 UN proper shipping name
- $\cdot ADR$

1173 ETHYL ACETATE

· IMDG, IATA

ETHYL ACETATE

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids.

- · Label
- · 14.4 Packing group
- · ADR, IMDG, IATA

II

(Contd. on page 8)

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

	(Contd. of pag
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F- E , S - D
Stowage Category	В
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1173 ETHYL ACETATE, , II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 9)

Printing date 03.08.2018 Version number 1 Revision: 24.01.2017

Trade name: GC RELINE II PRIMER FOR RESIN

(Contd. of page 8)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

GR ·