

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Heavy

Revision date: 17.05.2018

Product code: 001164

Page 1 of 4

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Identium Heavy

#### Further trade names

Identium Heavy  
Identium Heavy Fast

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

High viscosity, addition-curing, elastomeric precision impression material based on polyvinylsiloxane.  
For dental use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	Kettenbach GmbH & Co. KG	
Street:	Im Heerfeld 7	
Place:	D-35713 Eschenburg	
Telephone:	+ 49(0) 2774/705-0	Telefax: +49 (0)2774/705-66
e-mail:	info@kettenbach.com	
Contact person:	Regulatory Affairs Manager	Telephone: +49 (0)2774/705-0
Internet:	www.kettenbach.com	
Responsible Department:	Regulatory Affairs	

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

### 2.2. Label elements

#### Additional advice on labelling

There is no requirement for the product to be specially labelled according to EC directives or the corresponding national laws.

### 2.3. Other hazards

No risks worthy of mention.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Preparation of polyether- and silicone polymers, fillers, colorants and surfactants with platinum- catalyst (ppm-range).

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

not applicable

#### After contact with skin

In general the product is not skin irritative.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Heavy

Revision date: 17.05.2018

Product code: 001164

Page 2 of 4

#### After ingestion

Seek medical attention if problems persist.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>).

#### 5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Not required.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Take up mechanically.

#### 6.4. Reference to other sections

No release of hazardous substances.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

No special precautionary measures are necessary.

##### Advice on protection against fire and explosion

No special precautionary measures are necessary.

##### Further information on handling

No special precautionary measures are necessary.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

No special requirements.

##### Advice on storage compatibility

Not required.

##### Further information on storage conditions

No special requirements.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls

##### Appropriate engineering controls

not applicable

##### Protective and hygiene measures

The usual precautions when handling chemicals have to be obtained.

Avoid contact with skin, eyes and clothes.

##### Eye/face protection

Not required.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Heavy

Revision date: 17.05.2018

Product code: 001164

Page 3 of 4

#### Hand protection

Single-use gloves.

Suitable material: PE (polyethylene).

Unsuitable material: NR (Natural rubber (Caoutchouc), Natural latex).

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Not required.

#### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	Catalyst: grey-white. Base: light blue.
Odour:	odourless
pH-Value:	neutral

#### Changes in the physical state

Melting point:	not applicable
Initial boiling point and boiling range:	not applicable

#### Explosive properties

not Explosive.

Density (at 20 °C):	ca. 1,5 g/cm <sup>3</sup>
Water solubility:	insoluble

## SECTION 10: Stability and reactivity

### 10.4. Conditions to avoid

None by intended use.

### 10.5. Incompatible materials

None by intended use.

### 10.6. Hazardous decomposition products

None by intended use.

#### Further information

Please pay attention to the Directions for Use.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Acute toxicity, oral LD50: > 2000 mg/kg Rat

#### Irritation and corrosivity

Irritant effect on the skin: Not an irritant.

Irritant effect on the eye: Not an irritant.

#### Sensitising effects

no danger of sensitization.

## SECTION 12: Ecological information

### 12.1. Toxicity

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Heavy

Revision date: 17.05.2018

Product code: 001164

Page 4 of 4

product has not been tested.

#### Further information

Do not allow to enter into surface water or drains.

1 (slightly hazardous to water (WGK 1))

Doesn't get into the sewage water as long as the process is carried out according to regulations.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Remove according to the regulations.

##### Waste disposal number of waste from residues/unused products

070217 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; waste containing silicones other than those mentioned in 07 02 16

##### Waste disposal number of used product

200399 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; other municipal wastes; municipal wastes not otherwise specified

##### Contaminated packaging

Completely emptied packings can be re-cycled.

### SECTION 14: Transport information

#### Other applicable information

Not a hazardous material with respect to these transportation regulations.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

### SECTION 16: Other information

#### Changes

Update 2018-05-17

#### Further Information

@N16.P0000001

@N16.P0000002

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 1 of 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Identium Adhesive

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive for Identium® impression materials (Vinylsiloxanether®). Adheres to metals and acrylics.  
For dental use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	Kettenbach GmbH & Co. KG	
Street:	Im Heerfeld 7	
Place:	D-35713 Eschenburg	
Telephone:	+ 49(0) 2774/705-0	Telefax: +49 (0)2774/705-66
e-mail:	info@kettenbach.com	
Contact person:	Regulatory Affairs Manager	Telephone: +49 (0)2774/705-0
Internet:	www.kettenbach.com	
Responsible Department:	Regulatory Affairs	

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

May cause drowsiness or dizziness.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

ethyl acetate

butyl titanate (IV)

Signal word: Danger

Pictograms:



#### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 2 of 8

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P403+P235 Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No risks worthy of mention.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation based on silicone resin in organic solvents.

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
141-78-6	ethyl acetate			45 - < 50 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
1330-20-7	xylene			5 - < 10 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
100-41-4	ethylbenzene			1 - < 5 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
5593-70-4	butyl titanate (IV)			1 - < 5 %
	227-006-8			
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1; H226 H315 H318			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. Seek medical attention if problems persist.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

##### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

##### After ingestion

Vomiting Call a physician immediately.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 3 of 8

Sand.  
Extinguishing powder.

#### Unsuitable extinguishing media

Water.

#### 5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air.

#### 5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Wear personal protection equipment.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

#### 6.4. Reference to other sections

No release of hazardous substances.  
Personal protection equipment: see section 8

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Keep away from sources of ignition - No smoking.

##### Advice on protection against fire and explosion

Take precautionary measures against static discharges.

##### Further information on handling

No special precautionary measures are necessary.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool place.  
Store only in original container.

##### Further information on storage conditions

Protect against: heat.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 4 of 8

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

#### 8.2. Exposure controls

##### Protective and hygiene measures

Avoid contact with skin, eyes and clothes. Change contaminated clothing. Wash hands before breaks and after work. Protect skin by using skin protective cream.

##### Eye/face protection

Framed glasses.

##### Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Hand protection: Suitable material: Butyl rubber.

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Provide adequate ventilation.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	blue
Odour:	characteristic

##### Changes in the physical state

Initial boiling point and boiling range:	>70 °C
Flash point:	3 °C
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	11,5 vol. %
Ignition temperature:	> 400 °C
Vapour pressure: (at 20 °C)	< 102 hPa
Density (at 20 °C):	<1,1 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	practically insoluble

#### 9.2. Other information

Formation of potentially explosive vapor/air mixtures is possible.

### SECTION 10: Stability and reactivity

#### 10.4. Conditions to avoid

None by intended use.

#### 10.5. Incompatible materials

none



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 5 of 8

#### 10.6. Hazardous decomposition products

none

#### Further information

Highly flammable. Vapours may form explosive mixtures with air.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Irritant effect on the skin: Not an irritant.

Irritant effect on the eye: irritant.

Respiratory or skin sensitisation: no danger of sensitization.

##### ATEmix tested

	Dose	Species	Source
LD50, oral	>10000 mg/kg	Rat	

CAS No	Chemical name	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene	dermal	ATE 1100 mg/kg			
		inhalative vapour	ATE 11 mg/l			
		inhalative aerosol	ATE 1,5 mg/l			
100-41-4	ethylbenzene	oral	LD50 3500 mg/kg	@N11.P0000002	GESTIS	
		dermal	LD50 15400 mg/kg	@N11.P0000003	GESTIS	
		inhalative (4 h) vapour	LC50 17,2 mg/l	@N11.P0000002		
		inhalative aerosol	ATE 1,5 mg/l			

##### Additional information on tests

Preparation not tested. No data available.

##### Further information

Harmful by inhalation and if swallowed.

Hazards identification: Nausea. Headache. Vapours may cause drowsiness and dizziness.

After skin contact: Has de-greasing effect on the skin.

Following eye contact: Irritant.

Harmful: may cause lung damage if swallowed.

### SECTION 12: Ecological information

#### 12.1. Toxicity

CAS No	Chemical name	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
100-41-4	ethylbenzene	Acute algae toxicity	ErC50 3,6 mg/l	96 h		GESTIS	

#### 12.3. Bioaccumulative potential

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 6 of 8

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-41-4	ethylbenzene	3,15

#### Further information

Leakage into the environment must be prevented.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Do not remove with domestic waste. Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

##### Waste disposal number of used product

200399 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; other municipal wastes; municipal wastes not otherwise specified

##### Contaminated packaging

Cleaned containers may be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Excepted quantity:	E2
Transport category:	2
Hazard No:	33

#### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 7 of 8

Classification code: F1  
 Special Provisions: 640C  
 Limited quantity: 5 L  
 Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: -  
 Limited quantity: 5 L  
 Excepted quantity: E2  
 EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

### SECTION 16: Other information

#### Changes

Update 2018-05-17

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium Adhesive

Revision date: 17.05.2018

Product code: 226

Page 8 of 8

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

@N16.P0000001 @N16.P0000002

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*