

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066

Revision Date : 27.09.2019

Version : 1.1 /en

Replaces version from : 27.09.2019

Print date : 27.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name ModelSep

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Auxiliary for dental technology

1.3 Details of the supplier of the safety data sheet

Company designation HPdent GmbH
Erwin-Dietrich-Straße 5
78244 Gottmadingen
+49 7731 38 11 044
+49 7731 31 97 123
info@hpdent.com

Responsible Department During opening hours: +49 7731 38 11 044 Opening hours Mo – Th
from 8.30 a.m. to 5 p.m. / Fr from 08.30 a.m. to 4 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 Eye Irrit. 2
Narcotic effects Category 3
Flam. Liq. 2

2.2 Label elements

Hazard pictogram



GHS02



GHS05



GHS08



GHS07

Signal word

Danger

H-statement(s)

H226: Flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H373: Kann die Organe schädigen bei längerer oder wiederholter Exposition

P-statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271: Use only outdoors or in a well-ventilated area.

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066

Revision Date : 27.09.2019

Version : 1.1 /en



Replaces version from : 27.09.2019

Print date : 27.09.2019

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P233: Keep container tightly closed.

P241: Use explosion-proof (electrical/ventilating/lighting/ ...) equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P312: Call a POISON CENTER/doctor/ ... if you feel unwell.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).

P264: Wash ... thoroughly after handling.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

2.3 Other hazards

Health hazard

Avoid contact with skin, eyes and clothes.

Berufsübliche Hygienemaßnahmen einhalten.

Wiederholter Kontakt kann zu spröder oder rissiger Haut führen.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Ingredient	CAS No.	Classification (EC) 1272/2008	Concentration
Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)	CAS No. : 64742-89-8 EC-No. : 265-192-2		approx. 34.0 – 45.0 %
propan-2-ol; isopropyl alcohol; isopropanol	CAS No. : 67-63-0 EC-No. : 200-661-7 Index-No. : 603-117-00-0	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	approx. 25.0 – 35.0 %

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066

Revision Date : 27.09.2019

Version : 1.1 /en



Replaces version from : 27.09.2019

Print date : 27.09.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Where appropriate artificial ventilation. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
In case of skin contact	Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
In case of eye contact	In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
If swallowed	Do NOT induce vomiting. Let water be drunken in little sips (dilution effect). Consult physician.

4.2 Most important symptoms and effects, both acute and delayed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO ₂), alcohol resistant foam, Dry extinguishing powder
Extinguishing media which must not be used for safety reasons	Full water jet

5.3 Advice for firefighters

Special protective equipment for firefighting	Wear suitable coveralls to prevent exposure to the skin. In case of fire: Wear self-contained breathing apparatus.
---	--

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective gloves/protective clothing and eye/face protection. Respiratory protection at high concentrations.
----------------------	--

6.2 Environmental precautions

Environmental precautions	Do not allow to enter into surface water or drains. Avoid product spillage. Von Zündquellen fernhalten.
---------------------------	---

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	Keep away from sources of ignition. Absorb with paper towel or allow evaporation in hooded area. Flush area with water.
-------------------------	---

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Version : 1.1 /en

Replaces version from : 27.09.2019

Print date : 27.09.2019

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions Von Zündquellen fernhalten. Behälter dicht verschlossen halten.

Advice on protection against fire and explosion Keep away from sources of ignition – No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container requirements Keep only in the original container.

Recommended storage temperature bei Raumtemperatur

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

propan-2-ol; isopropyl alcohol; isopropanol

Germany					
Value / ppm	Value / mg/m ³	Ceiling Limit Value	Remarks	Issuing date	Source
200	500	2(II)	*1)	01/06	TRGS 900

*1): Senate Commission on the Testing of Health Hazardous Materials of the German Research Community. A risk of damage to the fruit need not be feared if the workplace limit value and the biological limit value (BGW) are observed.

Germany					
Germany	Parameter	Test material	Sampling time	Issuing date	Source
25 mg/l	Aceton	B	b	11/2012 DFG	TRGS 903
25 mg/l	Aceton	U	b	11/2012 DFG	TRGS 903

Denmark			
Value / ppm	Value / mg/m ³	Source	
200	490	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for ...	

Norway		
Value / ppm	Value / mg/m ³	Source
100	245	Veiledning om administrative normer for forurensning i arbeidsatmosfæ...

Sweden						
Long-term exposure value/ ppm	Long-term exposure value/ mg/m ³	Short-term exposure value/ ppm	Short-term exposure value/ mg/m ³	Issuing date	Note	Source
150	350	250	600	1989	V	HYGIENISKA GRÄNSVÄRDEN OCH ÅTGÄRDER

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

MOT LUFT-
FÖRORENINGAR
2011:18

Finland				
Long-term exposure value/ ppm	Long-term exposure value/ mg/m3	Short-term exposure value / ppm	Short-term exposure value / mg/m3	Source
200	500	250	620	HTTP-arvot 2012:5 HAITALLISIKSI TUN- NETUT PITOISUUDET

Poland		
Long-term exposure value/ mg/m3	Short-term exposure value / mg/m3	Source
900	1200	ROZPORZADZENIE MINISTRA PRACY I POLITYKI SPOLECZNEJ1) z dnia 16 cz- erw...

Austria								
Area of validity	Long-term exposure value/ ppm	Long-term exposure value/ mg/m3	Short-term exposure value / ppm	Short-term exposure value / mg/m3	Duration	Frequency per shift	Remarks	Source
MAK	200	500	800	2000	15(Miw)	4x		Stoffliste (MAK-Werte und TRK-Werte 2012)
MAK	200	500	800	2000	30(Miw)	4x	*1)	Stoffliste (MAK-Werte und TRK-Werte 2012)

*1): Short-term value for large-scale casting (valid until 31.12.2013)

Switzerland							
Long-term exposure value/ ppm	Long-term exposure value/ mg/m3	Short-term exposure value / ppm	Short-term exposure value / mg/m3	Notations	Critical toxicity	Source	
200	500	400	1000	B SSC	eye & OAW CNS liver	SUVA Switzerland 2017	

USA (ACGIH)				
Short term exposure limit	Long-term value	Basis	Remarks	Source
400 ppm	200 ppm	Irritation, CNS	Not classifiable as a Human Carcinogen	ACGIH Threshold Limit Values for Chemical Substances 2008

Spain

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

Long-term exposure value/ ppm	Long-term exposure value/ mg/m ³	Short-term exposure value / ppm	Short-term exposure value / mg/m ³	Note	Source
200	500	400	1000	VLB, s	Límites de exposición profesional para Agentes Químicos 2014

France					
Short-term exposure value / ppm	Short-term exposure value / mg/m ³	TMP n°	FT n°	Issuing date	Source
400	980	84	66	1982	Valeurs limites d'exposition professionnelle aux agents chimiques en ...

Belgium					
Long-term exposure value/ ppm	Long-term exposure value/ mg/m ³	Short-term exposure value / ppm	Short-term exposure value / mg/m ³	Source	
200	500	400	1 000	Liste de valeurs limites d'expositions professionnelle aux agents ...	

Great Britain					
Long-term exposure value/ ppm	Long-term exposure value/ mg/m ³	Short-term exposure value / ppm	Short-term exposure value / mg/m ³	Source	
400	999	500	1250	EH40/2005 Workplace exposure limits (2011)	

Czech Republic					
Long-term exposure value/ mg/m ³	Short-term exposure value / mg/m ³	Note	Source		
500	1000	I	NARÍZENÍ VLÁDY ze dne 12.prosince 2007 kterým se stanoví podmínky oc...		

Ireland					
Long-term exposure value/ ppm	Short-term exposure value / ppm	Remarks	Source		
200	400	Sk	Code of Practice for the Safety Health and Welfare at Work (2011)		

Hungary					
Long-term exposure value/ mg/m ³	Short-term exposure value / mg/m ³	Note	Remarks	Source	
500	2000	b, i	II.1.	25/2000. (IX. 30.) EüM-SzCsM együttes	

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

				rendelet a munkahelyek kémiai b...
--	--	--	--	------------------------------------

Estonia				
Long-term exposure value/ mg/m3	Long-term exposure value/ ppm	Short-term exposure value / mg/m3	Short-term exposure value / ppm	Source
350	150	600	250	Töökeskonna keemiliste ohuregurite piirnormid 11.10.2007 nr 223 (RT ...

Slovenia				
Long-term exposure value/ mg/m3	Long-term exposure value/ ppm	Ceiling Limit Value	Remarks	Source
500	200	4	Y, BAT	77

Lithuania				
Short-term exposure value / mg/m3	Short-term exposure value / ppm	Long-term exposure value/ mg/m3	Long-term exposure value/ ppm	Source
350	150	600	250	36

Bulgaria			
Long-term exposure value/ mg/m3	Short-term exposure value / mg/m3	Source	
980	1225	81	

Latvia			
Long-term exposure value/ mg/m3	Short-term exposure value / mg/m3	Source	
350	600	78	

Romania				
Long-term exposure value/ mg/m3	Long-term exposure value/ ppm	Short-term exposure value / mg/m3	Short-term exposure value / ppm	Source
200	81	500	203	79

Parameter	Sampling time	Source
50 mg/l Acetone in urine	End of shift	79

Greece				
Long-term exposure value/ mg/m3	Long-term exposure value/ ppm	Short-term exposure value / mg/m3	Short-term exposure value / ppm	Source
980	400	1225	500	80

PNEC	Target group	Exposure route	Remarks	Source
140,9 mg/l		PNEC aquatic, freshwater		Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

140,9 mg/l		PNEC aquatic, marine water		Company data
552 mg/kg		PNEC sediment, freshwater		Company data
552 mg/kg		PNEC sediment, marine water		Company data
28 mg/kg		PNEC soil		Company data
2251 mg/l		PNEC sewage treatment plant (STP)		Company data
140,9 mg/l		PNEC Environment, water, short-term (single):		Company data
	DNEL Consumer	DNEL Human, dermal, long-term (repeated):	(1 d)	Company data
	DNEL Consumer	DNEL Human, oral, long-term (repeated):	(1 d)	Company data
	DNEL worker	DNEL Human, dermal, long-term (repeated):	(1 d)	Company data

8.2 Exposure controls

Respiratory protection	Respiratory protection at high concentrations.
Hand protection	Wear protective gloves.
Suitable material	NBR (Nitrilkautschuk)
Eye protection	Wear solely goggles.
Skin and body protection	Usual hygienic measures of dental practice and dental laboratories.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	Petroleum
pH (min)	not determined
Boiling point [°C]	85 °C
Flash point [°C]	7x2 °C (TCC)
Flammability (solid, gas)	Entzündbar

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066

Revision Date : 27.09.2019

Version : 1.1 /en



Replaces version from : 27.09.2019

Print date : 27.09.2019

Explosion limits [Vol-%]

Lower limit 2,0

Upper limit 12,7

Relative density 0,83 g/ml @ 20 °C

Solubility insoluble

Viscosity, dynamic [kg/(m*s)] <2500 cP @ 23 °C

Viscosity, kinematic [mm²/s] >700 mm²/s @ 23 °C

SECTION 10: Stability and reactivity

10.2 Chemical stability

Chemical stability The product is stable under storage at normal ambient temperatures.

10.4 Conditions to avoid

Conditions to avoid Von Hitzequellen, Funken und offenen Flammen fernhalten.

10.5 Incompatible materials

Materials to avoid Carbon dioxide (CO₂), carbon monoxide, Hydro carbons

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Oral toxicity [mg/kg]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)				
Value	Test species	Exposure duration	Remarks	Source
>5.000	Mouse	LD50	Not applicable	Company data

propan-2-ol; isopropyl alcohol; isopropanol			
Value	Test criterion	Test species	Source
LD50 4570-5840 mg/kg	OECD 401	Rat	Company data

Dermal toxicity [mg/kg]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)				
Value	Test species	Duration	Remarks	Source
3.000	Rabbit	LD50	Acute toxicity Category 5	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

propan-2-ol; isopropyl alcohol; isopropanol			
Value	Test criterion	Test species	Source
LD50 13900 mg/kg	OECD 402	Rabbit	Company data

Inhalative toxicity [mg/l]

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol		
Value	Test species	Source
LC50 30 mg/l/4h	Rat	Company data

LC50 Inhalation 4h for gases [ppmV]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)	
Note	Source
No data available	Company data

LC50 Inhalation 4h for vapours [mg/l]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)	
Note	Source
No data available	Company data

LC50 Inhalation 4h for dusts and sprays [mg/l]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)	
Note	Source
No data available	Company data

Irritant effect on eyes

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol			
Value	Measuring method	Test species	Source
Eye Irrit. 2	OECD 405	Rabbit	Company data

Irritant effect on the respiratory tract

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol	
Value	Source
OECD 406; not sensitising.	Company data

Carcinogenic effects

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol		
Test species	Remarks	Source

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

Salmonella typhimurium.	negative.	Company data
-------------------------	-----------	--------------

Mutagenicity

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol		
Test species	Remarks	Source
Guinea pig	negative.	Company data

Reproduction toxicity

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol	
Remarks	Source
negative.	Company data

Caustic effect

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol			
Value	Measuring method	Test species	Source
Not an irritant.	OECD 404	Rabbit	Company data

Specific target organ toxicity (single exposure) [mg/kg]

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol	
Organs affected	Source
liver	Company data

Specific target organ toxicity (repeated exposure) [mg/kg]

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol		
Value	Route of exposure	Source
NOAEL(C): 900 mg/kg; Rat; OECD 408	oral	Company data

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish [mg/l]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)	
Remarks	Source
No data available	Company data

propan-2-ol; isopropyl alcohol; isopropanol				
Value	Test species	Exposure duration	Remarks	Source

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

LC50 >100 mg/l	Leuciscus idus (golden orfe)	96h	Persistence and degradability: 99,9 %; OECD 303A	Company data
----------------	------------------------------	-----	--	--------------

Toxicity to daphnia [mg/l]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)	
Remarks	Source
No data available	Company data

propan-2-ol; isopropyl alcohol; isopropanol			
Value	Test species	Exposure duration	Source
EC50: 2285 mg/l	Daphnia magna (Big water flea)	48h	Company data

Toxicity to algae [mg/l]

Hazardous ingredients

Solvent naphtha (petroleum), light aliph., not classified as carcinogenic (H350) and not classified as mutagenic (H340) and not classified as toxic for reproduction (H361fd)				
Value	Test species	Exposure duration	Measuring method	Source
4700	Selenastrum capricornutum	72 h	ErC50:	Company data

propan-2-ol; isopropyl alcohol; isopropanol				
Value	Test species	Exposure duration	Remarks	Source
EC50: >100 mg/l	Desmodesmus subspicatus	72h	*1)	Company data

*1): Persistence and degradability: 21 d; 95 %; OECD 301E

12.3 Bioaccumulative potential

Bioaccumulation

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol			
Value	Mobility	Remarks	Source
Log Pow	0,05	OECD 107	Company data

12.4 Mobility in soil

Mobility

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol	
Mobility	Source
soil: Koc; 1,1; Data obtained by expert judgement.	Company data

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066



Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol	
Value	Source
This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.	Company data

Toxicity to bacteria [mg/l]

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol		
Value	Test criterion	Source
EC50: >1000 mg/l	Activated sludge	Company data

Chemical Oxygen Demand (COD)

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol		
Value	Remarks	Source
96 %	Data arise from reference works and literature.	Company data

Biochemical Oxygen Demand (BOD)

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol	
Value	Source
53 %	Company data

Further information on ecology

Hazardous ingredients

propan-2-ol; isopropyl alcohol; isopropanol	
Value	Source
Theoretical oxygen demand (ThOD): 2,4 g/g	Company data

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1993	1993	1993

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name : ModelSep

Article-No. : 7065/7066






Revision Date : 27.09.2019

Replaces version from : 27.09.2019

Version : 1.1 /en

Print date : 27.09.2019

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group	II	II	II
14.2 Description of the goods	Flam. Liq.: Entzündbare Flüssigkeiten	Flam. Liq.: Entzündbare Flüssigkeiten	Flam. Liq.: Entzündbare Flüssigkeiten
Labels	3 - Flammable Liquid 	3 - Flammable Liquid 	3 - Flammable Liquid 
Proper shipping name	Flam. Liq.: Entzündbare Flüssigkeiten		
14.2 UN proper shipping name		Flam. Liq.: Entzündbare Flüssigkeiten	Flam. Liq.: Entzündbare Flüssigkeiten

SECTION 15: Regulatory information

SECTION 16: Other information

Relevant H-phrases

H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Wording of the hazard classes

Flam. Liq.: Flammable liquid
Eye Irrit.: Serious eye irritation
STOT SE: Specific target organ toxicity – single exposure

Further information

The information is based on present level of our knowledge. It does not however, give assurances of product properties and establishes no contract legal rights.
Die Angaben in diesem Sicherheitsdatenblatt entsprechen nach bestem Wissen unseren Erkenntnissen bei Drucklegung. Die Informationen sollen Ihnen Anhaltspunkte für den sicheren Umgang mit dem in diesem Sicherheitsdatenblatt genannten Produkt bei Lagerung, Verarbeitung, Transport und Entsorgung geben. Die Angaben sind nicht übertragbar auf andere Produkte. Soweit das Produkt mit anderen Materialien vermengt, vermischt oder verarbeitet wird, oder einer Bearbeitung unterzogen wird, können die Angaben in diesem Sicherheitsdatenblatt, soweit sich hieraus nicht ausdrücklich etwas anderes ergibt, nicht auf das so gefertigte neue Material übertragen werden.

Modifications of the previous version are denoted with an asterisk (*).

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.