

according to UK REACH Regulation

Issue date: 18/01/2023 Revision date: 18/01/2023 Supersedes: 20/07/2020 Version: 2.1

SDS No: 00056-0216



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : Softalind ViscoRub / Softa-Man ViscoRub

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1. Relevant identified uses

Use of the substance/mixture : Hand disinfectant

### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Manufacturer Supplier

B. Braun Medical AG B. Braun Medical Ltd.

Seesatz 17 Thorncliffe Park Estate, Brookdale Road

CH-6204 Sempach - Switzerland Sheffield S35 2PW, UK - Medical Information Department

T +41 (0) 58 / 258 50 00 T +44 (0)114 225 9000 info.bbmch@bbraun.com medinfo.bbmuk@bbraun.com

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

#### 1.4. Emergency telephone number

Emergency number : INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification according to GB CLP Regulation

Flammable liquids, Category 2

Serious eye damage/eye irritation, Category 1

H318

Specific target organ toxicity – Single exposure, Category 3, Narcosis

H336

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes serious eye damage. May cause drowsiness or dizziness.

# 2.2. Label elements

### Labelling according to GB CLP Regulation

Hazard pictograms (CLP)





GHS05



GHS02

GHS07

Signal word (CLP) : Danger Contains : Propan-1-ol

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.

H318 - Causes serious eye damage.

H336 - May cause drowsiness or dizziness.



according to UK REACH Regulation

SDS No: 00056-0216

Extra phrases

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P260 - Do not breathe vapours. P280 - Wear eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

**B** BRAUN

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER, a doctor.

P501 - Dispose of contents and container to an approved waste disposal plant.

Applies for those countries where this product is classified as medicinal product; as ready for use medicinal product, this product is not subject to labelling obligation according to the

CE directives in these countries.

Labelling according to: exemption for packages of a capacity of 125ml or less

Hazard pictograms (CLP)







GHS02

GHS05

GHS07

Signal word (CLP) : Danger Hazardous ingredients : Propan-1-ol

Hazard statements (CLP) H318 - Causes serious eye damage.

Precautionary statements (CLP) P280 - Wear eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER, a doctor.

P501 - Dispose of contents/container to an approved waste disposal plant.

Extra phrases Applies for those countries where this product is classified as medicinal product; as ready

for use medicinal product, this product is not subject to labelling obligation according to the

CE directives in these countries.

#### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

# 3.2. Mixtures

Comments : Alcoholic solution

Name	Product identifier		Classification according to GB CLP Regulation
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	< 80	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Propan-1-ol	(CAS-No.) 71-23-8 (EC-No.) 200-746-9 (EC Index-No.) 603-003-00-0 (REACH-no) 01-2119486761-29	< 25	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336



according to UK REACH Regulation

SDS No: 00056-0216



Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	(50 ≤ C ≤ 100) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general : Data of item 4 do partly not refer to the use and the regular employing of the product (in this sense consult package leaflet and expert information), but to liberation of major amounts in

poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek

medical advice.

First-aid measures after skin contact : No specific measures are necessary.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Consult an eye specialist.

First-aid measures after ingestion : Immediately give plenty of water. Rinse mouth. Call a physician immediately. Never give

anything by mouth to an unconscious person. Do not induce vomiting without medical

case of accidents and irregularities. Take off immediately all contaminated clothing. Call a

advice.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Serious damage to eyes.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Alcohol resistant foam. Carbon dioxide.

Unsuitable extinguishing media : high volume water jet.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Explosion hazard : Product is not explosive. Explosive vapour/air mixtures may be formed.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO2).

## 5.3. Advice for firefighters

Precautionary measures fire : Eliminate all ignition sources if safe to do so. Cool endangered containers with water spray

jet.

Firefighting instructions : Fight fire from safe distance and protected location.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Other information : Vapours are heavier than air and may spread along floors. Fire residues and contaminated

firefighting water must be disposed of in accordance with the local regulations.



according to UK REACH Regulation

SDS No: 00056-0216



# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill.

Methods for cleaning up : Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite. Notify authorities if

product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

Refer to protective measures listed in sections 7 and 8. For further information refer to section 13.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated

area. Avoid breathing vapours. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

roduct.

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Keep container tightly closed in a dry, cool and well-ventilated place.

Incompatible materials : alkali metals. alkaline earth metals. oxidizing materials. Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

See Section 1.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Ethanol (64-17-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m³
WEL TWA (OEL TWA) [2]	1000 ppm



according to UK REACH Regulation

SDS No: 00056-0216



Ethanol (64-17-5)	
WEL STEL (OEL STEL)	5760 mg/m³ (calculated)
WEL STEL (OEL STEL) [ppm]	3000 ppm (calculated)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Propan-1-ol (71-23-8)		
United Kingdom - Occupational Exposure Limits		
Local name	Propan-1-ol	
WEL TWA (OEL TWA) [1]	500 mg/m³	
WEL TWA (OEL TWA) [2]	200 ppm	
WEL STEL (OEL STEL)	625 mg/m³	
WEL STEL (OEL STEL) [ppm]	250 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Monitoring methods	
Monitoring methods	A specific exposure sampling method is not available
Biological monitoring methods	A specific exposure sampling method is not available

# 8.2. Exposure controls

## Appropriate engineering controls:

Ensure good ventilation of the work station.

# Personal protective equipment:

Data of item 8 do partly not refer to the use and the regular employing of the product (in this sense consult package leaflet and expert information), but to liberation of major amounts in case of accidents and irregularities.

# Hand protection:

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Butyl rubber	6 (> 480 minutes)	0,7		EN ISO 374

### Eye protection:

Eyewash bottle with clean water (EN 15154)

Туре	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

#### Skin and body protection:

Туре	Standard
Long sleeved protective clothing	EN ISO 6530



according to UK REACH Regulation

SDS No: 00056-0216



#### Respiratory protection:

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In the event of insufficient ventilation:	EN 14387

#### **Environmental exposure controls:**

Avoid release to the environment.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

рΗ : 8 Relative evaporation rate (butylacetate=1) : No data available : -114 °C Ethanol Melting point Freezing point : No data available **Boiling point** : 78 °C Ethanol Flash point : 21 °C DIN 51755 Auto-ignition temperature : 425 °C Ethanol Decomposition temperature : > 700 °C Ethanol Flammability (solid, gas) : Not applicable : 59 hPa Ethanol Vapour pressure : 2.07 Ethanol Relative vapour density at 20°C : No data available Relative density Density : 0.854 - 0.861 g/cm<sup>3</sup> Solubility : Miscible with water. : No data available Log Pow

Explosive properties : Product is not explosive. Explosive vapour/air mixtures may be formed.

: 200 - 600 mPa·s (25°C)

: No data available

Oxidising properties : Not oxidising.

Lower explosive limit (LEL) : 3.5 vol % Ethanol
Upper explosive limit (UEL) : 15 vol % Ethanol

### 9.2. Other information

Viscosity, kinematic

Viscosity, dynamic

VOC content : < 80 %

Additional information : Solvent content < 80 %

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Flammable liquid and vapour.

# 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reacts with: alkaline earth metals. alkali metals. oxidizing materials.

## 10.4. Conditions to avoid

Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited.



according to UK REACH Regulation

SDS No: 00056-0216



#### 10.5. Incompatible materials

alkali metals. alkaline earth metals. Oxidizing agent.

#### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg
LD50 oral	6200 mg/kg
LD50 dermal rabbit	15800 mg/kg
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat (Vapours)	30 mg/l/4h

Propan-1-ol (71-23-8)	
LD50 oral rat	> 8000 mg/kg
LD50 dermal rabbit	4032 mg/kg
LC50 Inhalation - Rat	> 33 mg/l 4 h

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: 8

Serious eye damage/irritation : Causes serious eye damage.

pH: 8

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Potential adverse human health effects and : Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing

symptoms properties of the product. At high concentrations, the vapours may cause narcosis.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecology - general : No ecotoxicological data about this product are known.

Hazardous to the aquatic environment, short-term : Not classified (Based on available data, the classification criteria are not met)

/acutal

Hazardous to the aquatic environment, long-term

: Not classified (Based on available data, the classification criteria are not met)

(chronic)



according to UK REACH Regulation

SDS No: 00056-0216



Ethanol (64-17-5)	
LC50 fish 1	11200 mg/l 96 h
EC50 Daphnia 1	5012 mg/l 48 h, Daphnia magna
ErC50 algae	275 mg/l

Propan-1-ol (71-23-8)	
LC50 fish 1	4555 mg/l 96 h, Pimephales promelas
EC50 Daphnia 1	3644 ml/l 48 h,Daphnia magna
NOEC chronic crustacea	> 100 mg/l 21 d, Daphnia magna
NOEC chronic algae	1150 mg/l 2 d,Chlorella sp.

# 12.2. Persistence and degradability

Softalind ViscoRub / Softa-Man ViscoRub	
Persistence and degradability	The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.

Propan-1-ol (71-23-8)	
BOD (% of ThOD)	75 % ThOD 20 d

# 12.3. Bioaccumulative potential

Ethanol (64-17-5)	
Bioconcentration factor (BCF REACH)	0.06
Log Pow	-0.3

# 12.4. Mobility in soil

No additional information available

# 12.5. Results of PBT and vPvB assessment

# Softalind ViscoRub / Softa-Man ViscoRub

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# 12.6. Other adverse effects

Other adverse effects : Slightly hazardous to water.

Additional information : Prevent entry to sewers and public waters



according to UK REACH Regulation

SDS No: 00056-0216



# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Can be incinerated according to local regulations. Recycling is preferred to disposal or

incineration.

Product/Packaging disposal recommendations : Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of

like the product.

European List of Waste (LoW) code : 07 06 04\* - other organic solvents, washing liquids and mother liquors

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number	14.1. UN number			
UN 1987	UN 1987	UN 1987	UN 1987	UN 1987
14.2. UN proper shippin	g name			
ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)	ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)	Alcohols, n.o.s. (Ethanol ; Propan-1-ol)	ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)	ALCOHOLS, N.O.S. (Ethanol ; Propan-1-ol)
Transport document descr	iption			
UN 1987 ALCOHOLS, N.O.S. (Ethanol ; Propan-1- ol), 3, II, (D/E)	UN 1987 ALCOHOLS, N.O.S. (Ethanol ; Propan-1- ol), 3, II	UN 1987 Alcohols, n.o.s. (Ethanol; Propan-1-ol), 3, II	UN 1987 ALCOHOLS, N.O.S. (Ethanol; Propan-1- ol), 3, II	UN 1987 ALCOHOLS, N.O.S. (Ethanol; Propan-1- ol), 3, II
14.3. Transport hazard	class(es)			
3	3	3	3	3
3	3	3	3	3
14.4. Packing group	14.4. Packing group			
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information	n available		I	1

# 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR) : F1

Special provisions (ADR) : 274, 601, 640D

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02, R001

Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 2
Hazard identification number (Kemler No.) : 33



# Safety Data Sheet

according to UK REACH Regulation

SDS No: 00056-0216

Orange plates :

33 1987

Tunnel restriction code (ADR) : D/E EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP1, TP8, TP28

EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-D Stowage category (IMDG) : B

Air transport

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) 1L PCA packing instructions (IATA) 353 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L Special provisions (IATA) : A3, A180 ERG code (IATA) : 31

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 274, 601, 640D

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E2

Carriage permitted (ADN) : T

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 274, 601, 640D

Limited quantities (RID) : 1L Excepted quantities (RID) : E2

Packing instructions (RID) : P001, IBC02, R001

Transport category (RID) : 2 Hazard identification number (RID) : 33

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

VOC content : < 80 %



according to UK REACH Regulation

SDS No: 00056-0216



# Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

# 15.1.2. National regulations

No additional information available

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

### Indication of changes:

All chapters have been modified since the previous version.

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IARC	International Agency for Research on Cancer
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
CAS	CAS (Chemical Abstracts Service) number
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Other information

: Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.



according to UK REACH Regulation SDS No: 00056-0216



Full text of H- and EUH-statements:		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
H225	Highly flammable liquid and vapour.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Classification and procedure used to derive the classification for mixtures according to GB CLP Regulation		
Flam. Liq. 2	H225	On basis of test data
Eye Dam. 1	H318	Calculation method
STOT SE 3	H336	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.